

Rotary Hammer

HR4511C

1 350 W • SDS-MAX • 45 mm • 9.4 J

Powerful dual-action combi hammer with anti-vibration technology for heavy-duty use

An efficient 1 350 W combi hammer with a unique AVT anti-vibration system for SDS-MAX blades. Masonry drilling capacity of 45 mm and impact energy of 9.4 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.



Technical specifications

Continuous Input Power	1350 W
No load speed	130 - 280 min ⁻¹
Impacts per Minute (IPM)	1250 - 2750 min ⁻¹
Max. Drilling Diameter in Concrete	45 mm
Optimum Drilling Diameter Range in Concrete	22 - 40 mm
Impact Energy	9,4 J
Drilling diameter with TCT core bit	125 mm
Power Supply Cord	5,0 m
Sound Power Level (L _{WA})	103 dB(A)
Sound Pressure Level (L _{pA})	95 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Chiselling	7,1 m/s ²
Weight Without Cable	8,5 kg
Product Dimensions (L x W x H):	458 x 136 x 288 mm

EAN 0088381084956

[Link to product - www.makita.com](http://www.makita.com)

User benefits

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- The service light indicates the need for carbon brush replacement and malfunctions in the switch and connection cable
- Impact drilling and spike function
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Constant speed control maintains constant speed under load



Related products

Optional AC

135209-6

Side Handle



194683-7

Grease vessel set, 100 ml



196188-3

Plastic Carrying Case

198993-4

Grease vessel for bit 100 ml



199144-2

Dust Extraction Attachment



321248-4

Depth Gauge



Other

[User manual](#)

[Parts drawing](#)